

Flood Lights



Type 'A'



Type 'B'



Type 'C'



Type 'D'



Type 'E'



Type 'F'



Type 'G'

Specifications

Fixtures:	Flood Lights						
Style	Type 'A'	Type 'B'	Type 'C'	Type 'D'	Type 'E'	Type 'F'	Type 'G'
Power Consumption:	50W	30W/50W	10W	100W/200W	320W	10W	30W
Lumen Output:	5000LM	3300/5500lm	1000lm	13000/26000lm	28800lm	Varies	3000lm
Beam Angle:	120°		120°	120°	120°	120°	120°
Voltage input:	100-277VAC	100-277VAC	120VAC	100-277VAC	100-277VAC	100-240VAC	100-277VAC
Color Temp:	30k, 40k, 57k	30k, 60k	30k, 40k, 57k	30k, 40k, 57k	30k, 40k, 60k	RGB	30k, 40k, 57k
Finishes:	Black/White	Brown	Brown	Brown	Brown	Brown	Brown
CRI:	≥75	>80	≥75	≥75	≥75	-	≥75
Driver	Meanwell	-	ES	Sosen	-	-	Sosen
IP65	✓	✓	IP54	✓	✓	✓	✓
Construction:	Aluminum		Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
ROHS	-	✓	-	-	-	-	-
cUL / cETL	cUL	cETL	cUL	cUL	cUL	cUL	cUL
LED Chip	Philips	Philips	Philips	Philips	Cree	Epistar	Philips
DLC Listed	-	✓	-	-	-	-	-
Warranty:	5 Year	5 Year	5 Year	5 Year	5 Year	5 Year	5 Year
Rated Life:	50,000hrs	50,000hrs	50,000hrs	50,000hrs	50,000hrs	50,000hrs	50,000hrs

Ordering Information:

Part #:	Type	Wattage	*Color CCT
WSLD-FL-	A	10	30K
	B	30	40K
	C	50	57K
	D	100	60K
	E	200	RGB
	F	320	
	G		

Example: WSLD-FL-D-200-57K

* Additional Color Temps may be available upon request.